

Performance Bulletin

25/07/2018





BOAT MANUFACTURER:

CAPELLI

BOAT MODEL:

TEMPEST 40

OUTBOARD:

XTO 425 Twin

TEST DATE:

Cantieri Capelli S.r.l. Italy www.cantiericapelli.com




PERFORMANCE DATA

RPM	Knots	L/Nm	Nm/L
700	3.0	3.3	0.3
1000	6.0	2.4	0.4
1500	8.5	2.4	0.4
2000	12.3	2.5	0.4
2500	18.0	2.4	0.4
3000	23.0	2.6	0.4
3500	28.0	3.0	0.3
4000	32.3	3.6	0.3
4500	38.0	4.0	0.3
5000	42.8	4.7	0.2
5500	47.0	5.5	0.2
5900	51.0	5.2	0.2

Acceleration time in seconds:

0-20 kn 5.1 s 0-30 kn 7.6 s



CAPELLI TEMPEST 40

Length	12.18	М
Beam	3.54	М
Dry Weight	3900	Kg
Max HP	850	HP
Fuel Capacity	650	L
Weight as Tested (approx.)	5800	Kg

XTO 425 Twin

Horsepower	425 Hp	313	Kw
Type & Displacement	Direct Injection	5559	CC
Configuration	V8 (60°), 32-valve, DO	HC witl	h VCT
Weight		453	Kg
Gear Ratio			1.79
Mounting Hole Position	48 mm	/	# 4

PROPELLER

Series		XTO
Diameter / Pitch	16 3/8 x	21
Partnumber	6GR-45976-	10-00

TEST CONDITIONS

Crew		5	prs.
Air Temperature		35	°C
Wind Speed		3	m/s
Fuel (98RON)		650	L
Type of water and temperature	Salt Water	27	°C

TEST PERFORMANCE SUMMARY

Max A	verage Speed	51	kn
Best C	ruising Nm/L	0.4	Nm/l
Range	e (95% fuel capacity & best Nm/L)	254	Nm

Comment: Tested weigth includes full tank of fuel, 3 battery, safety and test gear

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability.

Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase.

Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies.

Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.